

MDE-H04Lite

5MP HYBRID DVR



AHD · TVI · CVI · SD



Key Features

- WQHD 4채널 전용
- AHD+TVI+SD하이브리드
- 리얼 120프레임(라이브120프레임/저장60프레임)
- HDMI/VGA 동시모니터링
- 스마트폰 완벽지원

Dimention (Unit:mm)



Specification

SYSTEM	
Main processor	MC6630
Operation system	Embedded LINUX operation system
System resources	Multichannel real time record Multichannel real time playback Multichannel multi-user on network operation
INTERFACE	
Operation system	graphic menu operation interface, support mouse to operate
Image display	1/4/6/9/16 screen
Language	English, traditional Chinese, simplified Chinese, Japanese, Russian, German, Italian, Turkish, polish, Spanish, Korean, Indonesian, Thai, Arabic, Persian, Vietnamese, French, Portuguese, Greek, Czech
VIDEO	
Image coding	H.264/H.265
Surveillance quality	VGA(Max 1080P) ; HDMI(Max 1080P), CVBS optional
Preview	4*5MP-N@20fps/4*4MP-N@25fps/4*1080P@25fps
Code capacity	4*5 MP-N@12fps/4*4MP-N@17fps/4*1080P@15fps
Decode capacity	4*5 MP-N@12fps/4*4MP-N@17fps/4*1080P@15fps
Various mode input	Coaxial: 4*5MP-N Mixed: 4MP-N(coaxial)+1080P (IP) Arbitrary combination for coaxial and IP hybrid mode IP: 8*5MP, 16*5MP for all IP mode
Recognize method	Automatic Identification, All AHD, All TVI, All CVI, Customized
Motion detection	192 (16*12) testing areas can be set for each image ; can set multi-sensitivity (only for local channel and P6S IP camera)
AUDIO	
Audio compression	G.711U
Audio output	HDMI, support extended audio output.
Audio input intercom	Can extend to 4ch audio in. Support extend audio in and out intercom
RECORD & PLAYBACK	
Coaxial audio	Support 4ch coaxial audio
Video mode	manual>alarm>dynamic testing>timing
Local playback	1CH (5MP-N coaxial input)/4CH (4MP-N coaxial input) 2CH (Coaxial or Hybrid mode); 4ch IP mode
Record retrieval	Time retrieval, event retrieval, Timeline retrieval, channel retrieval Face playback, Intelligent playback(Motion detection playback)
STORAGE & BACKUP	
Occupation	1080P 10-15G/day*channel; 720P 10G/day*channel; 960H 6-10G/day*channel; Audio:691.2M/day*channel
Record storage	Local hard disk; network
Backup mode	Network backup, USB, SATA record
VMS	
Type	IE/mobile/VMS
p2p	Support(10S, Android, PC)
APP	Multi-screen surveillance; audio surveillance; mobile record; snap; pan-tilt control; remote record playback
UTC	
Camera OSD control	Support
Pan-tilt control	Don't support
3D-NR	Support auto/manual setting for noise reduction parameters
PORT	
Video input	4ch BNC; support coaxial audio in
Video output	1ch VGA , 1ch HDMI; 1ch TV output(Optional)
Audio output	HDMI output
Network port	RJ45 10M/100M Self-adapt to Ethernet interface
USB port	2 USB 2.0 port
HDD port	1 SATA Port (Can support 8T HDD)
Wifi port	NO
Remote control	Optional
OTHERS	
Power	12V/2A (Sufficient amperes)
Consumption	< 15W (exclusive hard disk)
Temperature	-5°C~ +55°C
Working humidity	10%~90%