

MDE-N5116-S2/16P



4K IP POE NVR



Key Features

- 4K 16채널 전용
- IP 16POE
- 오디오 단자1개
- HDMI/VGA 동시모니터링
- 스마트폰 HD완벽지원

Dimention



Specification

Processor	A1X
Operating System	Embedded LINUX Operating System
Operation Interface	Graphical operation interface, supporting mouse operation
Screen Display	1/4/6/9/16 screen
Video Input	16Ch//4K
Video Frame	NTSC@30 FPS , PAL@25 FPS
Video Output	VGA*1, HDMI*1
Image Decoding	H.264/H.265
Area Mask	Support (requires camera support)
Motion Detection	Support (requires camera support)
Human Detection	Support humanoid detection function (need to connect humanoid detection module)
Electronic fence Cross border detection Off duty detection	Supported, with alarm functions such as linkage push, large screen, and video recorder voice (requires front-end camera support)
Passenger flow statistics	Support for querying passenger flow data (requires front-end camera support)
Playback	Support AI human and vehicle shape playback functions for more accurate playback.
Audio Compression	G.711U G.711A G.726
Audio Input	According to the number of channels 1: 1 network audio input
Audio Output	Support HDMI audio output, 1ch 3.5mm audio output
Record Mode	Timing> Motion> Manual >Intelligent
Playback Channels	4 Ch 4K playback
Playback Mode	Time playback, browsing playback, intelligent event playback
Record Save	Hard disk, Network
Backup Method	USB removable hard disk, USB disk
PC	IE/VMS
APP(P2P)	Support(IOS, Android)
Video Output	1 VGA , 1 HDMI
Video Input	16 ch video input
Network	1 RJ45 100 / 1000M adaptive Ethernet interface
USB Interface	2USB 2.0 port
SATA Interface	2 SATA 2.0 Port, Max support 8TB HDD
PoE Interface	16 Ch PoE Port(Connect PoE camera)
PTZ Control	Control the front-end camera with PTZ device through the network
ONVIF	Support
Power Supply	DC 48V 3.75A
Working Humidity	10%~95%