

## CVR-N5132-S2

### 4K IP NVR



### Key Features

- 4K 32채널 전용
- IP NVR
- 리얼 120프레임(라이브120프레임)
- HDMI/VGA 동시모니터링
- 스마트폰 HD완벽지원

### Specification

<b>SYSTEM</b>	
MAIN CHIPSET	HI3536C
OS	Embedded Linux operating system
<b>INTERFACE</b>	
OPERATE INTERFACE	16 bits graphic interface, support mouse and keyboard operation
IMAGE DISPLAY	1/4/9/16/32 ch
VIDEO MODE	32ch 4K
<b>VIDEO</b>	
FRAME RATE	NTSC@30fps , PAL@25fps
VIDEO OUTPUT	VGA*1, HDMI*1
IMAGE DECODE	H.264/H.265/H.265+
AREA SHUTTER	support (needs the support of camera)
MOTION	support (needs the support of camera)
<b>AUDIO</b>	
FORMAT	G.711U G.711A G.726
TALKBACK	NO (optional)
INPUT	Audio input number is the same as channel number
OUTPUT	Support HDMI audio output, 1*RCV
<b>PLAYBACK</b>	
RECORD MODE	Timing, motion detection, record manually
PLAYBACK CHANNEL	1ch 8MP/4ch 2MP
RECORD RETRIEVAL	Time, event, and timeline, fast playback
<b>STORAGE BACKUP</b>	
RECORD SAVING	Local hard-disk, Network
BACKUP MODE	USB HDD、USB flash disk、CD writer
<b>REMOTE SURVEILLANCE</b>	
MOBILE SURVEILLANCE	Smartphone (iPhone, Android)
COMPUTER SURVEILLANCE	Support IE and easyVMS remote surveillance
<b>INTERFACE</b>	
VIDEO OUTPUT	1*VGA、1*HDMI
NETWORK	1*RJ45 100/1000M Ethernet interface self-adaption
ALARM	NO
AUDIO	1 RCA
RS485	NO
USB	2* USB 2.0 slots
HARD-DISK	2*SATA2.0 slots, each slot supports Max.6T
<b>OTHER</b>	
PAN-TILT CONTROL	Support pan-tilt control via network
ONVIF	support
POWER	DC12V 4A
CONSUMPTION	≤15W (PCB)
WORKING ENVIRONMENT	-10℃~+50℃ 10%~95%RH

### Dimention (Unit:mm)

